

HYELEC MS88 Digital multimeter

- Features:**

- 1.This instrument complies with IEC 61010-1, CAT. III 1000V and CAT.IV 600V overvoltage standards. See Specifications.
- 2.To get the best service from this instrument, read carefully this user's manual and respect the detailed safety precautions.



Specifications:

- 1.DC Voltage: 400mV/4V/40V/400V $\pm(0.5\%+3)$ /1000V $\pm(0.8\%+5)$
- 2.AC Voltage: 400mV $\pm(1.2\%+20)$ /4V/40V/400V $\pm(0.8\%+3)$ /750V $\pm(1.0\%+5)$
- 3.DC Current: 400 μ A/4000 μ A/40mA/400mA $\pm(1.0\%+5)$ /10A $\pm(1.5\%+8)$
- 4.AC Current: 400 μ A/4000 μ A/40mA/400mA $\pm(1.5\%+8)$ /10A $\pm(2.0\%+10)$
- 5.Resistance: 400 Ω /4k Ω /40k Ω /400k Ω /4M Ω $\pm(1.0\%+3)$ /40M Ω $\pm(1.2\%+15)$
- 6.Capacitance: 4nF/40nF/400nF/4 μ F/40 μ F/200 μ F $\pm(4.0\%+15)$
- 7.Frequency: 10Hz~10MHz $\pm(1.5\%+15)$
- 8.Duty cycle: 1%~99% $\pm(2.0\%+2)$
- 9.Display: 4000 Counts
- 10.Auto and manual range $\checkmark$
- 11.Relative Measurement $\checkmark$
- 12.Data hold $\checkmark$
- 13.Non-Contact Voltage Detector(NCV) $\checkmark$
- 14.Diode test $\checkmark$
- 15.Transistor $\checkmark$
- 16.Continuity $\checkmark$
- 17.Back light $\checkmark$
- 18.Power supply: 9V6F22 Battery(Battery Not Included)
- 19.Size:180mmx90mmx50mm
- 20.Safety Rating CE CAT.III1000V CAT.IV600V RoHS

INCLUDED: 1 * HYELEC MS88 Multimeter(Battery Not Included)
1 * Set of Test Cable